



Dual end cap M/F DDF

End cap for duct D



Top quality galvanized
steel 275 g/m²

Description

End cap for duct "spiro" - "D" (duct, fitting) and dual end cap male/female (duct) - "DDF", are made from top quality galvanized steel (275 g/m²). Fully automated stamping process from one metal sheet.

Technical drawing DDF



Dimensions DDF [mm]

Ød nom	Ød	ØD	h	H	pcs/box	box type
80	78,8	81,5	30	60	60	P24
100	98,8	101,5	30	60	100	P24
125	123,8	126,5	30	60	27	P24
150	148,8	151,5	30	60	40	P12
160	158,8	161,5	30	60	32	P12
200	198,8	201,5	30	60	22	P12
250	248,8	251,5	30	60	32	P6
315	313,8	316,5	30	60	25	P6
355	353,8	356,5	30	60	23	P6
400	398,8	401,5	30	60	24	P6

Technical drawing D



Dimensions D [mm]

ØD nom	H	R	kg	pcs/box	box type
80	20	5	0,04	175	P24
100	20	5	0,08	125	P24
125	20	5	0,09	80	P24
150	20	5	0,14	60	P24
160	20	5	0,14	110	P12
200	20	5	0,2	70	P12
250	20	5	0,27	50	P12
315	20	5	0,51	40	P12
355	20	5	0,65	30	P12
400	20	5	0,67	50	P4
450	50	-	1,14	40	P1
500	65	-	1,46	33	P1



Packaging method on page 38