

Trough and mounting fittings PVC



Description


Installation trough used for air conditioning installation. They allow you to mask cooling lines and condensate drains in an aesthetic way. PVC material in two colours Optimal Duct – pure white and ARTICA DUCT - creamy white. Increased resistance for UV radiation and mechanical damage. Wide temperature range -20°C +60°C.



Installation trough PVC

ODF 80
ADF 80

Technical drawing



Technical specifications [mm]

Model	A	B	Length	Quantity in the box [pcs.]
ODF 80	80	60	2000	8
ADF 80	80	60	2000	8

Trough end cap PVC

ODEC 80
CLEC 80



Technical specifications [mm]

Model	Width	Height	Quantity in the box [pcs.]
ODEC 80	80	60	10
CLEC 80	80	60	10

Wall-mounted cover PVC

ODWC 80
CLWC 80



Technical specifications [mm]

Model	Width	Height	Quantity in the box [pcs.]
ODWC 80	80	60	10
CLWC 80	80	60	10



Connecting strap PVC, tray connector


ODC 80
CLC 80

Technical specifications [mm]

Model	Width	Height	Quantity in the box [pcs.]
ODC 80	80	60	10
CLC 80	80	60	10

Inner corner PVC

ODIC 80
CLIC 80



Technical specifications [mm]

Model	Width	Height	Quantity in the box [pcs.]
ODIC 80	80	60	10
CLIC 80	80	60	10