



## Zinc spray for ventilation ducts

Zinc spray designed for (cold electroplating.) Protects all metal surfaces from corrosion. Creates an even layer that can be painted or left as final protection. Ideal for retouching, finishing or repairing galvanised elements. Used on metal surfaces: iron, aluminium, steel.

### Technical specifications

Box	12 pcs.
Volume	400 ml
Pressure in 20°C	5,5 bar
Color	Light grey/aluminium
Capacity	2 - 3 m <sup>2</sup>
Drying time in 20°C	Surface: 10 minutes Touch-dry: 20 minutes For use: 6 hrs Applying successive coatings after 12 hrs



## Soudal Acryrub grey acrylic

An acrylic dispersion-based sealant with excellent adhesion to all porous substrates used in construction: brick, concrete, wood, stone, plasterboard, etc. It does not contain solvents and is odorless. After drying, it can be painted and varnished. Suitable for both indoor and outdoor use.

### Technical specifications

Base	Acrylic dispersion
Volume	310 ml
Consistency	Paste
Curing system	Physical drying
Drying time	Approx. 20 minutes (at 20°C / 65% RH)
Density	1,7 g/cm <sup>3</sup> (depending on the color)
Application temperature	From +5°C to +30°C
Thermal resistance	From -20°C to +80°C
Maximum allowable deformation	Approx. 15%
Shrinkage after curing	Approx. 15%
Color	Grey
Resistance to sagging	≤ 3 mm
Volume loss	≤ 25%
Elastic recovery	< 40%
Standards and certifications	ISO 9001 SCAQMD Reg. 1168 USGBC LEED® 2009 v.4.1 (VOC)

## Grey silicone TIGER



For sealing and filling the openings around the ventilation ducts.

### Technical specifications

Model	Thermal resistance	Volume	Box
Grey silicone TIGER	-50°C to +120°C	260 ml	24 pcs.

## Mounting foam TIGER



For filling cracks and gaps in connections.

### Technical specifications

Model	Volume	Box
Mounting foam FOAM 750 (tube)	750 ml	12 pcs.
Mounting foam GUN FOAM 750 (gun)	750 ml	12 pcs.