

# Male coupling with gasket NPL



Rounded, reinforced  
"SAFE" edges



Double gasket,  
tightness class D



Automatic linear  
welding




Top quality  
galvanised steel  
275 g/m<sup>2</sup>

## Description

Male coupling with gasket "NPL" **SAFE**, made from top quality galvanised steel (275 g/m<sup>2</sup>). Automated linear welding process. With every edge "SAFE" type - reinforced with curved rims, provide additional fitting rigidity and safe mounting. Double gasket EPDM clamped automatically ensures no risk of slipping during mounting. Product with tightness class D - every single bend undergoes air tightness test in the factory.

## Technical drawing



## Dimensions [mm]

Ød nom	H	kg	pcs/box	box type
80	40	0,12	80	P12
100	40	0,15	112	P6
125	40	0,19	81	P6
150	40	0,22	45	P6
160	40	0,24	70	P4
200	40	0,3	50	P4
250	40	0,37	63	P2
315	40	0,47	36	P2
355	40	0,5	55	P1
400	40	0,67	50	P1
450	55	0,95	20	P1
500	55	1,06	18	P1
560	55	1,19	16	P1
600	55	1,29	16	P1
630	70	2,01	14	P1
710	70	2,26	10	P1
800	70	3,9	7	P1
900	70	4,6	-	-
1000	100	6,2	-	-



Packaging method on page 38