



Segmented bends BF i BFE



Automatic linear welding








Top quality galvanised steel 275 g/m²

Description

Segmented bends - BF i BFE, are made from top quality galvanised steel (275 g/m²).

Technical drawing



Dimensions BF90 i BFE90 [mm], Angle 90°

Ød nom	l	t	kg	pcs/box	box type
250	250	0,5	1,80	54	
315	315	0,5	2,60	28	layered packing + stretch film
355	355	0,5	3,30	21	
400	400	0,6	4,90	12	
450	450	0,6	6,00	-	-
500	500	0,7	8,70		on request
560	560	0,7	10,60		on request
630	630	0,7	14,10		on request
710	710	0,7	17,90		on request
800	800	0,7	21,50		on request
900	900	0,9	32,00		on request
1000	1000	0,9	46,10		on request

Dimensions BF45 i BFE45 [mm], Angle 45°

Ød nom	l	t	kg	pcs/box	box type
250	105	0,5	1,07	96	
315	130	0,5	1,55	48	layered packing + stretch film
355	145	0,5	1,86	42	
400	165	0,6	2,80	30	
450	185	0,6	3,67	-	-
500	205	0,7	5,28		on request
560	230	0,7	5,92		on request
630	260	0,7	7,25		on request
710	295	0,7	9,57		on request
800	330	0,7	11,35		on request
900	375	0,9	22,80		on request
1000	410	0,9	27,57		on request

Dimensions BF15 i BFE15 [mm], Angle 15°

Ød nom	l	t	kg	pcs/box	box type
250	35	0,5	0,64	25	P2
315	45	0,5	0,92	30	P1
355	50	0,5	0,99	20	P1
400	55	0,6	1,40	20	P1
450	60	0,6	2,30	-	-
500	70	0,7	3,43	-	-
560	75	0,7	3,96	-	-
630	85	0,7	4,79	-	-
710	95	0,7	6,43		on request
800	110	0,7	7,05		on request
900	120	0,9	8,20		on request
1000	135	0,9	10,50		on request



Packaging method on page 38

Dimensions BF30 i BFE30 [mm], Angle 30°

Ød nom	l	t	kg	pcs/box	box type
250	70	0,5	0,73	40	P1
315	85	0,5	1,17	10	P2
355	95	0,5	1,47	8	P2
400	110	0,6	2,03	10	P1
450	120	0,6	2,71	-	-
500	135	0,7	3,77	-	-
560	150	0,7	4,24	-	-
630	170	0,7	5,51	-	-
710	190	0,7	7,25	-	-
800	220	0,7	8,73	-	on request
900	240	0,9	16,96	-	on request
1000	270	0,9	20,36	-	on request

Dimensions BF60 i BFE60 [mm], Angle 60°

Ød nom	l	t	kg	pcs/box	box type
250	145	0,5	1,30	10	P2
315	185	0,5	1,80	10	P1
355	205	0,5	2,20	8	P1
400	235	0,6	3,20	4	P1
450	260	0,6	4,00	-	-
500	290	0,7	5,60	-	on request
560	325	0,7	6,80	-	on request
630	365	0,7	8,40	-	on request
710	410	0,7	14,00	-	on request
800	465	0,7	16,90	-	on request
900	520	0,9	19,10	-	on request
1000	580	0,9	24,00	-	on request



Packaging method on page 38